

Han B Base Panel 1 Lever Thermoplastic C



| Part number | 09 30 010 0303 |
|--------------------|--|
| Specification | Han B Base Panel 1 Lever Thermoplastic C |
| HARTING eCatalogue | https://b2b.harting.com/09300100303 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|-----------------------------|---------------------------|
| Series of hoods/housings | Han [®] B |
| Type of hood/housing | Bulkhead mounted housing |
| Description of hood/housing | With thermo-plastic cover |
| Туре | Low construction |

Version

| Size | 10 B |
|----------------------------|---|
| Locking type | Single locking lever |
| Han-Easy Lock [®] | Yes |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|--|
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Mating cycles | ≥500 |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-------------------------|--------------------|
| Surface (hood/housing) | Powder-coated |

Page 1 / 2 | Creation date 2024-10-30 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany

Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

| Colour (hood/housing) | RAL 7037 (dust grey) |
|--|---|
| Material (seal) | NBR |
| Material (locking) | Polycarbonate (PC) Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |
| ECHA SCIP number | a4a9de28-6060-4c0d-b79b-5842f7db41be |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |
| | |

Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E235076 |
|-----------|-----------------------------------|
| | CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals | CE |
| | DNV GL |
| | |

Commercial data

| Packaging size | 1 |
|--------------------------------|--|
| Net weight | 100 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140044463 |
| ETIM | EC000437 |
| eCl@ss | 27440202 Shell for industrial connectors |