

DSUB FE STR SOLDER CONTACT 75 OHMS COAX



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 69 181 5230 |
| Specification | DSUB FE STR SOLDER CONTACT 75 OHMS COAX |
| HARTING eCatalogue | https://b2b.harting.com/09691815230 |

Identification

| | |
|----------------------------|--|
| Category | Contacts |
| Series | D-Sub |
| Identification | Mixed |
| Type of contact | Coaxial contact |
| Description of the contact | Straight for cables RG 179 BU, 187 AU |
| Features | Outer ferrule: crimp in tool cavity B |

Version

| | |
|-----------------------|--------------------------|
| Termination method | Solder/crimp termination |
| Gender | Female |
| Manufacturing process | Turned contacts |

Technical characteristics

| | |
|-----------------------|--|
| Rated current | ≤ 2 A |
| Rated voltage | 250 V |
| Insulation resistance | $> 10^9 \Omega$ |
| Contact resistance | 2.7 m Ω for inner contact die 2.7 m Ω for outer ferrule |
| Impedance | 75 Ω |
| Stripping length | 3 mm for inner contact die 5 mm Shielding 9.5 mm cable jacket |
| Limiting temperature | -55 ... +135 °C |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---------------------------|-----------------|
| Insertion force | ≤7 N |
| Withdrawal force | ≤7 N |
| Performance level | NM 30 (S4) 1 |
| Mating cycles | ≥500 |
| Test voltage $U_{r.m.s.}$ | 0.75 kV @ 50 Hz |
| Frequency | 0 ... 2 GHz |

Material properties

| | |
|--------------------------------------|--|
| Material (contacts) | Copper alloy PBFE / PBTP / PI |
| Surface (contacts) | Noble metal over Ni |
| Layer thickness | ≥0.76 μm |
| Layer thickness | ≥30 μinch |
| Material (locking) | Copper alloy |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | ecef7555-f643-4ceb-a337-fc54762297f1 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Commercial data

| | |
|--------------------------------|---------------|
| Packaging size | 20 |
| Net weight | 2.26 g |
| Country of origin | Czechia |
| European customs tariff number | 85366990 |
| GTIN | 5713140096714 |
| ETIM | EC000796 |



Pushing Performance
Since 1945

Commercial data

eCl@ss

27440204 Contact for industrial connectors