TE Internal #: 1-1414476-0

High Current Relay, DC, Monostable, 1 Form A (NO), 130 A Contact

Rating, 12 VDC Coil Voltage, 12 VDC Contact Voltage, 3.9 W Coil

Power, Panel Mount

View on TE.com >



Relays & Contactors > Electromechanical Relays











Relay & Contactor Type: High Current Relay

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form A (NO)

Current Type: DC

Contact Current Rating: 130 A

Features

Product Type Features

Relay & Contactor Type	High Current Relay
Configuration Features	
Coil Special Features	Resistor in Parallel
Contact Arrangement	1 Form A (NO)
Electrical Characteristics	
Contact Limiting Making Current	300 A
Contact Limiting Continuous Current	180 A
Contact Limiting Breaking Current	300 A
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Switching Load (Min)	1000mA @ 5V
Coil Resistance	37 Ω
Contact Current Rating	130 A
Coil Voltage Rating	12 VDC
Contact Voltage Rating	12 VDC



Insulation Initial Dielectric Between Contacts & Coil Body Features Product Weight 220 gl7.76 oz J Finclosure Type Flux Resistant Automatic Solder Capable Washable Contact Features Contact Material Silver Alloy Termination Features Main Termination & Connection Type M6 Male Coil Termination & Connection Type Wire Connector Mechanical Attachment Product Mounting Feature Type Mounting Brackets Product Mount Type Panel Mount Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range 40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC Other	oil Power Rating DC	3.9 W
Product Weight 220 g/7.76 oz Enclosure Type Flux Resistant Automatic Solder Capable Washable Contact Features Contact Material Silver Alloy Termination Features Main Termination & Connection Type M6 Male Coil Termination & Connection Type Wire Connector Mechanical Attachment Product Mounting Feature Type Mount Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range 40 – 125 °C[40 – 257 °F] Environmental Category of Protection RTIII Froirmmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	sulation Initial Dielectric Between Contacts & Coil	1000 Vrms
Find Resistant Automatic Solder Capable Washable Contact Features Contact Material Silver Alloy Termination Features Main Termination & Connection Type M6 Male Coil Termination & Connection Type Wire Connector Mechanical Attachment Product Mounting Feature Type Mounting Brackets Product Mount Type Panel Mount Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range 40 – 125 °C[-40 – 257 °T] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °T] Operation/Application Coil Magnetic System Monostable Current Type DC	ly Features	
Contact Material Silver Alloy Termination Features Main Termination & Connection Type M6 Male Coil Termination & Connection Type Wire Connector Mechanical Attachment Product Mounting Feature Type Mounting Brackets Product Mount Type Panel Mount Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	oduct Weight	220 g[7.76 oz]
Contact Material Fermination Features Main Termination & Connection Type M6 Male Coil Termination & Connection Type Wire Connector Mechanical Attachment Product Mounting Feature Type Mounting Brackets Product Mount Type Panel Mount Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range Environmental Category of Protection Environmental Ambient Temperature (Max) Coil Magnetic System Monostable Current Type M6 Male Wire Connector Mounting Brackets Panel Mount 40 mm[1.575 in] 74.2 mm[2.921 in] 74.2 mm[2.921 in] 74.2 mm[2.921 in] 74.2 mm[2.921 in] 75.2 C[-40 – 257 °F] Operation/Application	closure Type	Flux Resistant Automatic Solder Capable & Washable
Termination Features Main Termination & Connection Type	tact Features	
Main Termination & Connection Type Coil Termination & Connection Type Wire Connector Mechanical Attachment Product Mounting Feature Type Product Mount Type Product Mount Type Product Width Product Length Product Length Product Height Usage Conditions Operating Temperature Range Environmental Category of Protection Environmental Ambient Temperature (Max) Coil Magnetic System Monostable Current Type Mount Mounting Brackets Mounting Brackets Panel Mount Mounting Brackets Panel Mount Advantage Panel Mount 40 mm[1.575 in] Fanel Renge Product Height 45 mm[1.772 in] Usage Conditions Operation/Application Coil Magnetic System Monostable DC	ontact Material	Silver Alloy
Coil Termination & Connection Type Mechanical Attachment Product Mounting Feature Type Mounting Brackets Product Mount Type Panel Mount Dimensions Product Width 40 mm[1.575 in] Product Length Product Length 45 mm[2.921 in] Usage Conditions Operating Temperature Range Environmental Category of Protection Environmental Ambient Temperature (Max) Coil Magnetic System Monostable Current Type Wire Connector Wire Connector Wire Connector Wire Connector Wire Connector Mounting Brackets Mounting Brackets Panel Mount 40 mm[1.575 in] 74.2 mm[2.921 in] 74.2 mm[2.921 in] Froduct Height 45 mm[1.772 in] Usage Conditions Operation/Application Coil Magnetic System Monostable DC	nination Features	
Mechanical Attachment Product Mounting Feature Type Mounting Brackets Product Mount Type Panel Mount Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range 40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	ain Termination & Connection Type	M6 Male
Product Mounting Feature Type Panel Mount Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	oil Termination & Connection Type	Wire Connector
Product Mount Type Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	chanical Attachment	
Dimensions Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	oduct Mounting Feature Type	Mounting Brackets
Product Width 40 mm[1.575 in] Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	oduct Mount Type	Panel Mount
Product Length 74.2 mm[2.921 in] Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range -40 - 125 °C[-40 - 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	ensions	
Product Height 45 mm[1.772 in] Usage Conditions Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	oduct Width	40 mm[1.575 in]
Usage Conditions Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	oduct Length	74.2 mm[2.921 in]
Operating Temperature Range -40 – 125 °C[-40 – 257 °F] Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	oduct Height	45 mm[1.772 in]
Environmental Category of Protection RTIII Environmental Ambient Temperature (Max) 125 °C[257 °F] Operation/Application Coil Magnetic System Monostable Current Type DC	ge Conditions	
Environmental Ambient Temperature (Max) Operation/Application Coil Magnetic System Monostable Current Type DC	perating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application Coil Magnetic System Monostable Current Type DC	vironmental Category of Protection	RTIII
Coil Magnetic System Current Type DC	vironmental Ambient Temperature (Max)	125 °C[257 °F]
Current Type DC	eration/Application	
	oil Magnetic System	Monostable
Other	ırrent Type	DC
	er	
Coil Power Rating Class >3 − ≤10 W	oil Power Rating Class	>3 - ≤10 W
Contact Current Class >50 − ≤200 A	ontact Current Class	>50 - ≤200 A
Height Class (Mechanical) >33 - ≤45 mm[>1.299 - ≤1.772 in]	eight Class (Mechanical)	>33 - ≤45 mm[>1.299 - ≤1.772 in]
Length Class (Mechanical) >70 mm[>2.756 in]	ngth Class (Mechanical)	>70 mm[>2.756 in]
Width Class (Mechanical) >33 mm[>1.299 in]	dth Class (Mechanical)	>33 mm[>1.299 in]



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Customers Also Bought





TE Part #AS610-98PC
PLUG BOOT TERMIN'N TYPE 6









TE Part #1-1414632-0 V23132B2002X025-EV-CBOX










TE Part #7-1414778-3 V23130C2421A431-EV-CBOX



Documents

Product Drawings

V23132A2001X023-EV-CBOX

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1414476-0_A.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1414476-0_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1414476-0_A.3d_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

High Current Relay, DC, Monostable, 1 Form A (NO), 130 A Contact Rating, 12 VDC Coil Voltage, 12 VDC Contact Voltage, 3.9 W Coil Power, Panel Mount



High Current Relay 150, High Current Devices, High Current Solutions

English