



Fuse-link, high speed, 16 A, AC 690 V, 200 kA, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC



Part no. **FUSE 16A 690V 000U/80 GR UC**
 Catalog No. **170M1309**

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 16 |
| Rated voltage | | | AC 690 V |
| Construction size | | | DIN 000 |
| Size | | | 21 x 40 x 100 mm |
| Utilization category | | | gR |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | DIN IEC |
| Shape | | | square body with offset bolted tags (slotted) |
| Standards/Regulations | | | DIN 43653 IEC 60269-4 |

Technical data ETIM 8.0

| | | | |
|--|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl:ss10.0.1-27-14-20-90 [BAB264011]) | | | |
| Fuse construction type according to IEC 60269 | | | Other |
| Type of current | | | |
| Rated voltage AC | | V | 690 |
| Rated voltage DC | | V | |
| Rated current | | A | 16 |
| Utilization category | | | gR (general purpose semiconductor protection) |
| Breaking capacity | | kA | |
| Colour code | | | |
| Type of fuse status indicator | | | None |
| Power loss at rated current | | W | 5.5 |
| Mounting holes | | | |
| Centre-to-centre distance of connections | | mm | |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720013_170M.pdf |
|-------------------------|---|