



**Fuse-link, high speed, 100 A, AC 690 V, 200 kA, size 000, 24 x 36 x 96 mm, aR, IEC, visual indicator**



**Part no. FUSE 100A 690V 000F/70 AR UR**  
**Catalog No. 170M1517**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	100
Rated voltage			AC 690 V
Construction size			size 000
Size			24 x 36 x 96 mm
Utilization category			aR
Status indicator			visual indicator
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with offset bolted tags
Standards/Regulations			IEC 60269-4

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	100
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf">http://www1.cooperbusmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf</a>
-------------------------	---