## Fuse-link, high speed, 32 A, AC 690 V, DIN 000, gR, DIN, IEC, dual indicator, live gripping lugs $\,$



## 170M1562D

General specifications	
Product name	Eaton Bussmann series high speed square body fuse
Part no.	170M1562D
EAN	5027590441247
Product Length/Depth	79 millimetre
Product height	51 millimetre
Product width	21 millimetre
Product weight	135.8 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Recognized IEC Rated
Product Tradename	None
Product Type	High speed square body fuse
Product Sub Type	None
electrical data	
Amperage Rating	32 A
Voltage rating	690 V (IEC), 700 V (UL)
Interrupt rating	200 kAIC
Class	Class gR
Clearing (I2T)	285 at 660 V
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type	DIN 43620 Bladed
Fuse indicator	Combination fuse status indicator
Fuse size	000

## **Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])					
Fuse construction type according to IEC 60269			000		
Type of current			AC		
Rated voltage AC	V	/	690		
Rated voltage DC	V	/			
Rated current	A	4	32		
Utilization category			gR (general purpose semiconductor protection)		
Breaking capacity	k	κA	200		
Colour code			None		
Type of fuse status indicator			Combination fuse status indicator		
Power loss at rated current	V	N	7		
Mounting holes					
Centre-to-centre distance of connections	n	nm			