



Fuse-link, high speed, 35 A, AC 1000 V, 125 kA, DIN 00, aR, DIN, IEC, type T indicator, live gripping lugs

Part no. **FUSE 35A 1000V DIN 00 AR**
 Catalog No. **170M2676**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	35
Rated voltage			AC 1000 V
Construction size			DIN 00
Utilization category			aR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	125
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			00
Type of current			AC
Rated voltage AC		V	1000
Rated voltage DC		V	
Rated current		A	35
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	125
Colour code			None
Type of fuse status indicator			Other
Power loss at rated current		W	12
Mounting holes			
Centre-to-centre distance of connections		mm	

Additional product information (links)

High-speed full-line catalogue (pdf)	http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf
--------------------------------------	---