



Fuse-link, high speed, 250 A, AC 690 V, 200 kA, compact DIN 1, 45 x 58 x 134 mm, aR, DIN, IEC, single indicator, 80 mm fixing centres



Part no. **FUSE 250A 690V 1*TN/110 AR UC**
 Catalog No. **170M3216**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	250
Rated voltage			AC 690 V
Construction size			compact DIN 1
Size			45 x 58 x 134 mm
Utilization category			aR
Status indicator			single indicator
Description			80 mm fixing centres
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	250
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No