



Fuse-link, high speed, 200 A, AC 690 V, compact size 1, 45 x 59 x 51 mm, aR, IEC, UL, M8, square body with flush end contacts



Referencia **FUSE 200A 690V 1\*BN/50 AR UC**  
 Catalog No. **170M3415**

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	200
Rated voltage			AC 690 V
Construction size			compact size 1
Size			45 x 59 x 51 mm
Utilization category			aR
Status indicator			single indicator
Description			M8
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

### Technical data ETIM 7.0

Tipo de corriente			EV000460
Tensión nominal CA			690
Corriente nominal			200
Categoría de uso			EV005309
Capacidad de desconexión			200
Código de color			EV000494
Tipo de indicador de estado de fusible			EV007782

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720019_170M.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720019_170M.pdf</a>
-------------------------	---