



Fuse-link, high speed, 200 A, AC 690 V, 200 kA, compact size 1, aR, IEC, UL, type K indicator



Part no. **FUSE 200A 690V 1*BKN/50 AR UC**
 Catalog No. **170M3465**

Delivery program

| | | | |
|------------------------------|---|----|-------------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 200 |
| Rated voltage | | | AC 690 V |
| Construction size | | | compact size 1 |
| Utilization category | | | aR |
| Status indicator | | | type K indicator |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | IEC UL |
| Shape | | | square body with flush end contacts |
| Standards/Regulations | | | IEC 60269-4 |

Technical data ETIM 8.0

| | | | |
|--|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | | |
| Fuse construction type according to IEC 60269 | | | Other |
| Type of current | | | AC |
| Rated voltage AC | | V | 690 |
| Rated voltage DC | | V | |
| Rated current | | A | 200 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Breaking capacity | | kA | 200 |
| Colour code | | | None |
| Type of fuse status indicator | | | Other |
| Power loss at rated current | | W | 35 |
| Mounting holes | | | M8 |
| Centre-to-centre distance of connections | | mm | 50 |