



Fuse-link, high speed, 550 A, AC 690 V, 200 kA, compact size 1, aR, IEC, UL, type K indicator



Part no. **FUSE 550A 690V 1\*BKN/50 AR UC**  
 Catalog No. **170M3472**

**Delivery program**

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	550
Rated voltage			AC 690 V
Construction size			compact size 1
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

**Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	550
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No

**Additional product information (links)**

High-speed full-line catalogue (pdf)	<a href="http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf">http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf</a>
--------------------------------------	---