



Fuse-link, high speed, 630 A, AC 1000 V, 150 kA, DIN 1, 51 x 69 x 138 mm, aR, DIN, IEC, type T indicator



Part no. **FUSE 630A 1000V 1TN/110 AR**
 Catalog No. **170M4989**

Delivery program

| | | | |
|------------------------------|---|----|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 630 |
| Rated voltage | | | AC 1000 V |
| Construction size | | | DIN 1 |
| Size | | | 51 x 69 x 138 mm |
| Utilization category | | | aR |
| Status indicator | | | type T indicator |
| Breaking Capacity | | kA | 150 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | DIN IEC |
| Shape | | | square body with centre-bolted tags (slotted) |
| Standards/Regulations | | | DIN 43653 IEC 60269-4 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 630 |
| Rated voltage | | V | 1000 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 125 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | Top fuse status indicator |
| Insulated metal gripping lugs (IMGL) | | | No |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720059_Square_Body_DIN_43_654.pdf |
|-------------------------|---|