

Eaton 170M5442

Catalog Number: 170M5442

Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 x 77 x 81 mm, aR, IEC, UL, single indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M5442
	UPC
	051712261289
EAN	Product Length/Depth
5027590457149	92 mm
Product Height	Product Width
60 mm	163 mm
Product Weight	Warranty
818 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

400 A

Breaking capacity

100 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

2

Rated voltage AC

1250 V

Center-to-center distance of connections

80.3 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

140000 at 1000 V, 180000 at 1250 V

Watt losses

85 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Pre arc (I2T)

23000

Color

None

Interrupt rating

100 kAIC

Fitted with:

Type K Indicator for micro

Construction size

2

Mounting method

Flush

Packaging type

Standard

Voltage rating

1250 V (IEC), 1300 V (UL)

Fuse type

Flush end

BKN/80 Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)