



Fuse-link, high speed, 500 A, AC 690 V, 200 kA, size 2, 61 x 77 x 135 mm, aR, IEC, UL, type K indicator, US style, 90 mm fixing centres

Part no. **FUSE 500A 690V 2FKE/90 AR UC**
Catalog No. **170M5660**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	500
Rated voltage			AC 690 V
Construction size			size 2
Size			61 x 77 x 135 mm
Utilization category			aR
Status indicator			type K indicator
Description			US style 90 mm fixing centres
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with centre-bolted tags
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	500
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No