



Válcová pojistka, Vysokorychlostní, 800 A, AC 1100 V, 100 kA, size 2, 61 x 77 x 160 mm, aR, IEC, UL, americký styl

Typ FUUSE 800A 1100V 2FU/115 AR
Catalog No. 170M5698

Dodavatelský program

Produktový sortiment			Pojistka
Základní funkce			Válcová pojistka
Oblast aplikace			Vysokorychlostní
Stanovený proud	I	A	800
Jmenovité napětí			AC 1100 V
Konstrukční velikost			size 2
Velikost			61 x 77 x 160 mm
Kategorie užití			aR
Popis			americký styl
Vypínací zatížitelnost		kA	100
použitelné pro velikost / aplikace			ochrana polovodičů
Standardní / schválení			IEC UL
Tvar			čtvercové tělo se středovými konci s otvory na šroub
Standardní/Regulace			IEC 60269-4

Technická data podle ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])			
Fuse system according to IEC 60269			Other
Fuse construction type according to IEC 60269			2
Type of current			AC
Rated voltage AC		V	1100
Rated voltage DC		V	
Rated current		A	800
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	100
Colour code			None
Type of fuse status indicator			None
Power loss at rated current		W	120
Mounting holes			M12
Centre-to-centre distance of connections		mm	115