



Fuse-link, high speed, 700 A, AC 1250 V, 100 kA, size 3, 76 x 92 x 76 mm, aR, IEC, UL, square body with flush end contacts

Part no. **FUSE 700A 1250V 3GKN/75 AR CU**  
 Catalog No. **170M6595**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	700
Rated voltage			AC 1250 V
Construction size			size 3
Size			76 x 92 x 76 mm
Utilization category			aR
Status indicator			type K indicator
Description			US thread
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	700
Rated voltage		V	1250
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No