



Fuse-link, 550 A, AC 2500 V, 100 kA, size 3, 86 x 95 x 166 mm, aR, IEC, type K indicator

Part no. FU5E 550A 2500V 3BKN/170 AR
Catalog No. 170M6643

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	550
Rated voltage			AC 2500 V
Construction size			size 3
Size			86 x 95 x 166 mm
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	550
Rated voltage		V	2500
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No