Fuse-link, high speed, 1400 A, AC 1000 V, size 3, 76 x 92 x 159 mm, aR, IEC, UL, single indicator



## 170M6751

Similar to illustration

eneral specifications	
Product name	Eaton Bussmann series high speed square body fuse
Part no.	170M6751
EAN	5996516020630
Product Length/Depth	168 millimetre
Product height	76 millimetre
Product width	95 millimetre
Product weight	1301 gram
Compliances	CE Marked RoHS Compliant
Certifications	CSA Certified IEC Rated UL Recognized
Product Tradename	None
Product Type	High speed square body fuse
Product Sub Type	None
lectrical data	
Amperage Rating	1400 A
Voltage rating	1000 V
Interrupt rating	100 kAIC
Class	Class aR
Clearing (I2T)	6000000 at 1000 V
roduct specifications	
Application	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type	US Style FKE/115 Type K indicator for micro Bolted tag
Fuse indicator	Centre fuse status indicator
Fuse size	3

## **Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])			
Fuse system according to IEC 60269		Other	
Fuse construction type according to IEC 60269		3	
Type of current		AC	
Rated voltage AC	V	1000	
Rated voltage DC	V		
Rated current	А	1400	
Utilization category		aR (accompanied semiconductor protection)	
Breaking capacity	kA	100	
Colour code		None	
Type of fuse status indicator		Centre fuse status indicator	
Power loss at rated current	W	150	
Mounting holes		Other	
Centre-to-centre distance of connections	mm	114	