



Fuse-link, high speed, 200 A, AC 660 V, DIN 0, aR, DIN, IEC, single indicator, live gripping lugs

170M7919

General specifications		
Product name		Eaton Bussmann series high speed square body fuse
Part no.		170M7919
EAN		5027590464611
Product Length/Depth		125 millimetre
Product height		60 millimetre
Product width		35 millimetre
Product weight		289.8 gram
Compliances		EAC CE RoHS Compliant
Certifications		IEC 60269-4
Product Tradename		None
Product Type		High speed square body fuse
Product Sub Type		None
Electrical data		
Amperage Rating		200 A
Voltage rating		660 V
Interrupt rating		100 kAIC
Class		Class aR
Product specifications		
Application		semiconductor protection
Fuse type		DIN 43620 Bladed
Fuse indicator		Top fuse status indicator
Fuse size		0

### Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		0
Type of current		AC
Rated voltage AC	V	660
Rated voltage DC	V	
Rated current	A	200
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	100
Colour code		None
Type of fuse status indicator		Top fuse status indicator
Power loss at rated current	W	35
Mounting holes		
Centre-to-centre distance of connections	mm	