DATASHEET - FUSE 800A 690V 3SHT AR UC



Fuse-link, high speed, 800 A, AC 690 V, size 3, 76 x 76 x 150 mm, aR, IEC, single indicator



Part no. FUSE 800A 690V 3SHT AR UC Catalog No. 170M8545

Similar to illustration

Delivery program			
Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	1	Α	800
Rated voltage			AC 690 V
Construction size			size 3
Size			76 x 76 x 150 mm
Utilization category			aR
Status indicator			single indicator
usable for size/applications			Protection of power rectifiers
Standard/Approval			IEC
Shape			square body with special bladed contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installat	ion, device / Safety fuse	inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269		3
Type of current		AC
Rated voltage AC	V	690
Rated voltage DC	V	
Rated current	Α	800
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		Other
Power loss at rated current	W	
Mounting holes		
Centre-to-centre distance of connections	mm	