DATASHEET - FUSE 1600A 690V 3SHT AR UC



Fuse-link, high speed, 1600 A, AC 690 V, size 3, 76 x 76 x 150 mm, aR, IEC, single indicator



Part no. FUSE 1600A 690V 3SHT AR UC 170M8550

Similar to illustration

General specifications	
Product name	Eaton Bussmann series high speed square body fuse
Part no.	FUSE 1600A 690V 3SHT AR UC
EAN	5996516022344
Product Length/Depth	168 millimetre
Product height	76 millimetre
Product width	95 millimetre
Product weight	1061 gram
Compliances	Contact factory RoHS Compliant
Product Tradename	None
Product Type	High speed square body fuse
Product Sub Type	None
Electrical data	
Amperage Rating	1600 A
Voltage rating	690 V
Interrupt rating	200 kAIC
Class	Class aR
Product specifications	
Application	Protection of power rectifiers
Fuse type	T indicator for micro
Fuse indicator	Top fuse status indicator
Fuse size	3

Technical data ETIM 9.0

Toomitour data 2 mm olo		
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation	n, device / Safety fuse	inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		3
Type of current		AC
Rated voltage AC	V	690
Rated voltage DC	V	
Rated current	А	1600
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		Top fuse status indicator
Power loss at rated current	W	160
Mounting holes		
Centre-to-centre distance of connections	mm	