



Fuse-link, high speed, 1000 A, AC 1000 V, DIN 3, 90 x 75 x 150 mm, aR, DIN, IEC, single indicator, live gripping lugs

Part no. FUSE 1000A 1000V DIN 3 AR UR
Catalog No. 170M8650

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1000
Rated voltage			AC 1000 V
Construction size			DIN 3
Size			90 x 75 x 150 mm
Utilization category			aR
Status indicator			single indicator
Description			live gripping lugs
usable for size/applications			Protection of power rectifiers
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			3
Type of current			AC
Rated voltage AC		V	1000
Rated voltage DC		V	
Rated current		A	1000
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	100
Colour code			None
Type of fuse status indicator			Top fuse status indicator
Power loss at rated current		W	
Mounting holes			
Centre-to-centre distance of connections		mm	