



Fuse-link, high speed, 180 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS

**180MMT**

Similar to illustration

<b>General specifications</b>		
Product name		Eaton Bussmann series high speed british standard fuse
Part no.		180MMT
EAN		5027590036269
Product Length/Depth		98 millimetre
Product height		40 millimetre
Product width		97 millimetre
Product weight		478 gram
Compliances		CE Marked RoHS Compliant
Certifications		UL Recognized IEC Rated IEC 60269-4 Designed and tested to BS88 part 4 UL recognized
Product Tradename		None
Product Type		High speed british standard fuse
Product Sub Type		None
<b>Electrical data</b>		
Amperage Rating		180 A
Voltage rating		690 V (IEC), 700 V (UL)
Rated voltage AC		690 V
Rated voltage DC		350 V
Interrupt rating		200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)
Class		Class aR
Clearing (I <sub>ZT</sub> )		12000
Watt losses		42 W
<b>Product specifications</b>		
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse indicator		None
<b>Compatible Trip indicator/microswitch</b>		
Suitable for		MC-700 Trip indicator kit (indicator + clips) TI700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

**Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	690
Rated voltage DC	V	350
Rated current	A	180
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None

Type of fuse status indicator		None
Power loss at rated current	W	42
Mounting holes		M8
Centre-to-centre distance of connections	mm	85