



Fuse-link, high speed, 200 A, AC 240 V, DC 150 V, BS88, 38 x 84 mm, aR, BS

200LMT

| General specifications                |  |   |
|---------------------------------------|--|---|
| Product name                          |  | Eaton Bussmann series high speed british standard fuse  |
| Part no.                              |  | 200LMT  |
| EAN                                   |  | 5027590037006   |
| Product Length/Depth                  |  | 84 millimetre   |
| Product height                        |  | 41 millimetre   |
| Product width                         |  | 39 millimetre   |
| Product weight                        |  | 185 gram  |
| Compliances                           |  | RoHS Compliant<br>CE Marked   |
| Certifications                        |  | UL recognized<br>Designed and tested to BS88 part 4<br>CCC<br>IEC 60269-4<br>UL Recognized<br>IEC Rated                     |
| Product Tradename                     |  | None  |
| Product Type                          |  | High speed british standard fuse  |
| Product Sub Type                      |  | None  |
| Electrical data                       |  |   |
| Amperage Rating                       |  | 200 A   |
| Voltage rating                        |  | 240 Vac, 150 Vdc  |
| Rated voltage AC                      |  | 240 V   |
| Rated voltage DC                      |  | 150 V   |
| Interrupt rating                      |  | 200 kA RMS Sym, 50 kA at 150 Vdc (UL)<br>200 kA RMS Sym, 40 kA at 150 Vdc (IEC)   |
| Class                                 |  | Class aR  |
| Clearing (I <sub>ZT</sub> )           |  | 20000   |
| Watt losses                           |  | 28 W  |
| Product specifications                |  |   |
| Application                           |  | Semiconductor, DC Common bus, DC drives, power converters/rectifiers  |
| Fuse indicator                        |  | None  |
| Compatible Trip indicator/microswitch |  |   |
| Suitable for                          |  | MBI Microswitch/adaptor<br>MAI Microswitch/adaptor<br>TI250 Fuse indicator<br>MC-250 Trip indicator kit (indicator + clips) |

Technical data ETIM 9.0

| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)   |    |   |
|---|----|---|
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ec@ss13-27-14-20-90 [BAB264016]) |    |   |
| Fuse system according to IEC 60269  |    | Other                                     |
| Fuse construction type according to IEC 60269   |    | Other                                     |
| Type of current   |    | AC/DC                                     |
| Rated voltage AC  | V  | 240                                       |
| Rated voltage DC  | V  | 150                                       |
| Rated current   | A  | 200                                       |
| Utilization category  |    | aR (accompanied semiconductor protection) |
| Breaking capacity   | kA | 200                                       |
| Colour code   |    | None                                      |
| Type of fuse status indicator   |    | None                                      |
| Power loss at rated current   | W  | 28  |

|  |    |      |
|--|----|------|
| Mounting holes                           |    | M10  |
| Centre-to-centre distance of connections | mm | 58.2 |