



## NOTES:

## MATERIALS:

- 1. INSULATORS = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
  2. LOCKWASHER = PHOSPHOR BRONZE PER ASTM B139, COPPER ALLOY C53400, TEMPER H04.
  3. ALL OTHER METAL PARTS = BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.

## FINISHES:

- 1. CONTACTS = GOLD PLATE PER ASTM B488-01, TYPE II, 50µin MIN, GRADE C, OVER 100 TO 200µin STRESS FREE SULFAMATE NICKEL PER QQ-N-290.
  2. ALL OTHER METAL PARTS = GOLD PLATE PER ASTM B488-11, TYPE II, 30µin MIN, GRADE C OVER 100 TO 200µin COPPER STRIKE PER AMS 2418.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		DWN: DATE D.N. 03/09/18 CHKD: DATE		Property of Radiall This document cannot be reproduced or communicated to a third party without prior veritten permission of RADIALL.
DECIMAL	ANGLE	C.E. 03/09/18		RIGHT ANGLE MALE JACK
		APVD: DATE	31110	BULKHEAD MOUNT
		J.M. 03/09/18		P.C.B. RECEPTACLE
REFERENCE:		MATERIALS & FINISHES:	SIZE FSCM NO	the state of the s
ORIGINATED: D.N.		SEE NOTES	A 19505	2110-1511-000 🗚
DATE: 03/09/18			SCALE 5:1	THIRD ANGLE SHEET 1 OF 1