



Fuse-link, high speed, 280 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS

**280MMT**

Similar to illustration

General specifications		
Product name		Eaton Bussmann series high speed british standard fuse
Part no.		280MMT
EAN		5027590039604
Product Length/Depth		110 millimetre
Product height		83 millimetre
Product width		39 millimetre
Product weight		478 gram
Compliances		RoHS Compliant CE Marked
Product Tradename		None
Product Type		High speed british standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		280 A
Voltage rating		690 V (IEC), 700 V (UL)
Rated voltage AC		690 V
Rated voltage DC		350 V
Interrupt rating		200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)
Class		Class aR
Clearing (I <sub>ZT</sub> )		47000
Watt losses		47 W
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse indicator		None
Compatible Trip indicator/microswitch		
Suitable for		MC-700 Trip indicator kit (indicator + clips) TI700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

**Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / Fusible HRC (EC004556)		
Tecnología electrónica, de automatización y de mando de procesos / Instalación eléctrica, equipo / Inserto de fusibles / Inserto de fusibles (sin clasificación) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	690
Rated voltage DC	V	350
Rated current	A	280
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	47
Mounting holes		M8

