

400FMM

General specifications		
Product name		Eaton Bussmann series high speed British standard fuse
Part no.		400FMM
EAN		5027590046824
Product Length/Depth		112 millimetre
Product height		38 millimetre
Product width		83 millimetre
Product weight		452 gram
Compliances		CE Marked RoHS Compliant
Certifications		UL Recognized IEC Rated CCC Designed and tested to BS88 part 4 IEC 60269-4 UL recognized
Product Tradename		None
Product Type		High speed British standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		400 A
Voltage rating		690 V AC
Rated voltage AC		690 V
Rated voltage DC		450 V
Interrupt rating		200 kA RMS Sym (IEC/UL), 40 kA at 450 Vdc (IEC)
Class		Class aR
Clearing (I ₂ T)		40000
Watt losses		85 W
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse indicator		None
Compatible Trip indicator/microswitch		
Suitable for		MC-600 Trip indicator kit (indicator + clips) TI700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ec@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	690
Rated voltage DC	V	450
Rated current	A	400
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	85

Mounting holes		M8
Centre-to-centre distance of connections	mm	83.7