



Fuse-link, LV, 100 A, AC 415 V, BS88/B1, 26 x 126 mm, gM, BS, 100M160

Catalog No. **CD100M160**

### Delivery program

|                              |   |    |                                 |
|------------------------------|---|----|---------------------------------|
| Product range                |   |    | Fuse                            |
| Basic function               |   |    | Fuse-link                       |
| Field of application         |   |    | low voltage                     |
| Rated current                | I | A  | 100                             |
| Motor current rating         | I | A  | 100M160                         |
| Rated voltage                |   |    | AC 415 V                        |
| Construction size            |   |    | BS88/B1                         |
| Size                         |   |    | 26 x 126 mm                     |
| Utilization category         |   |    | gM                              |
| Description                  |   |    | motor-rated                     |
| Breaking Capacity            |   | kA | 80                              |
| usable for size/applications |   |    | general industrial applications |
| Standard/Approval            |   |    | BS                              |
| Shape                        |   |    | centre-bolted tags              |
| Standards/Regulations        |   |    | BS88-2<br>IEC 60269-2           |
| Optional accessories         |   |    | fuse-holder RS200               |

### Technical data ETIM 7.0

|   |  |    |       |
|---|--|----|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |       |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |       |
| Construction size   |  |    | Other |
| Rated current   |  | A  | 100   |
| Rated voltage   |  | V  | 415   |
| Voltage type  |  |    | AC    |
| Rated switching capacity  |  | kA | 80    |
| Utilization category  |  |    | Other |
| Type of fuse status indicator   |  |    | None  |
| Insulated metal gripping lugs (IMGL)  |  |    | No    |

### Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (pdf) | <a href="http://www1.cooperbusmann.com/pdf/f8417af7-9f84-4ac5-a79d-b86f6e5b3603.pdf">http://www1.cooperbusmann.com/pdf/f8417af7-9f84-4ac5-a79d-b86f6e5b3603.pdf</a> |
|-------------------------|---|