



Fuse-link, low voltage, 1.4 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, time-delay

Part no. **BUSS MIDGET FUSE**
 Catalog No. **FNM-1-4/10**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	1.4
Rated voltage			AC 250 V
Size			10 x 38 mm
Utilization category			supplemental
Description			colour-coded green
usable for size/applications			general purpose, lighting circuits, meter circuits
Release characteristic	class		time-delay
Standard/Approval			UL CSA
Shape			cylindrical
Material			melamine tube
Standards/Regulations			UL 248-14

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			10x38 mm
Rated voltage		V	250 - 250
Rated voltage			Other
Voltage type			AC
Utilization category			Other
Rated operating frequency		Hz	45 - 62
Nominal current		A	1.4
With striker			No
Release characteristic			M (Midget)
Breaking capacity		kA	0.1

Assets (links)

Declaration of CE Conformity

00003283

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_2028_FNM.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/time_delay_midget/fnm.html