



Fuse-link, high speed, 200 A, AC 500 V, DC 500 V, 200 kA, 29 x 92 mm, aR, UL

Part no. **200A 500V AC TAG FUSE**  
 Catalog No. **FWH-200B**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	200
Rated voltage			AC 500 V DC 500 V
Size			29 x 92 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			centre-bolted tags
Standards/Regulations			UL 248
Optional accessories			fuse-holder BH series

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			AC/DC
Rated voltage AC		V	500
Rated voltage DC		V	500
Rated current		A	200
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	200
Colour code			White
Type of fuse status indicator			None
Power loss at rated current		W	40
Mounting holes			M8
Centre-to-centre distance of connections		mm	74.09