



Fuse-link, high speed, 300 A, AC 500 V, 200 kA, 38 x 110 mm, UL

Part no. BUSS HIGH SPEED FUSE
Catalog No. FWH-300A

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	300
Rated voltage			AC 500 V
Size			38 x 110 mm
Breaking Capacity		kA	200
usable for size/applications			DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical with centre-bolted tags
Standards/Regulations			UL 248

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	300
Rated voltage		V	500
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720007_FWH-(35-1600)A.pdf
-------------------------	---