



Fuse-link, high speed, 30 A, AC 500 V, 50 kA, 14 x 51 mm, aR, UL

Part no. **30AMP 500V AC FERRULE 14x51mm**  
 Catalog No. **FWH-30A14F**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	30
Rated voltage			AC 500 V
Size			14 x 51 mm
Utilization category			aR
Breaking Capacity		kA	50
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL 248

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			14x51 mm
Rated voltage		V	500 - 500
Rated voltage			Other
Voltage type			AC/DC
Utilization category			aR (accompanied semiconductor protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	30
With striker			No
Release characteristic			Other
Breaking capacity		kA	200