

Fuse-link, high speed, 12 A, AC 690 V, 10 x 38, gR, IEC, UL



FWP-12G10F

General specifications	
Product name	Eaton Bussmann series high speed cylindrical fuse
Part no.	FWP-12G10F
EAN	5027590500180
Product Length/Depth	38 millimetre
Product height	10 millimetre
Product width	10 millimetre
Product weight	7.6 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Recognized IEC Rated
Product Tradename	None
Product Type	High speed cylindrical fuse
Product Sub Type	None
Electrical data	
Amperage Rating	1200 A
Voltage rating	500 V
Voltage type	AC
Interrupt rating	200 kAIC
Class	Class gR
Clearing (I2T)	84
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator	Other
Fuse size	10 x 38 mm
Compatible microswitch	
Accessories	CHM modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])					
Model			Ceramic fuse		
Size			10x38 mm		
Voltage type			AC		
Rated current	A	A	1200		
Rated voltage	V	/	500		
Utilization category			gR (general purpose semiconductor protection)		
Rated operating frequency	H	Hz	45 - 62		
Type of fuse status indicator			Other		
Release characteristic			Other		
Breaking capacity	k	κA	200		

Power loss at rated current W 2.99