



Fuse-link, high speed, 20 A, AC 700 V, 22 x 58 mm, aR, UL

FWP-20A22F

Similar to illustration

General specifications		
Product name		Eaton Bussmann series high speed cylindrical fuse
Part no.		FWP-20A22F
EAN		5027590500319
Product Length/Depth		56 millimetre
Product height		23 millimetre
Product width		23 millimetre
Product weight		55.7 gram
Compliances		CE Marked RoHS Compliant
Certifications		CSA Certified UL Recognized
Product Tradename		None
Product Type		High speed cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		20 A
Voltage rating		700 V
Voltage type		AC/DC
Interrupt rating		200 kAIC
Class		Class aR
Clearing (I ₂ T)		330
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator		Other
Fuse size		22 x 58 mm
Quantity		10
Compatible microswitch		
Accessories		JM70100 Fuse base

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC/DC
Rated current	A	20
Rated voltage	V	700
Utilization category		aR (accompanied semiconductor protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	200
Power loss at rated current	W	5