



Fuse-link, high speed, 20 A, AC 700 V, DC 700 V, 15 x 73 mm, aR, UL

**FWP-20B**

Similar to illustration

<b>General specifications</b>		
Product name		Eaton Bussmann series high speed cylindrical fuse
Part no.		FWP-20B
EAN		5027590500333
Product Length/Depth		73 millimetre
Product height		15 millimetre
Product width		15 millimetre
Product weight		24.5 gram
Compliances		RoHS Compliant CE Marked
Certifications		CSA Certified UL Recognized
Product Tradename		None
Product Type		High speed cylindrical fuse
Product Sub Type		None
<b>Electrical data</b>		
Amperage Rating		20 A
Voltage rating		700 Vac, 700 Vdc (UL)
Voltage type		AC/DC
Interrupt rating		200 kAIC Vac 50 kAIC at 700 Vdc 200 kAIC at 300 Vdc 50 kAIC at 300 Vdc
Class		Class aR
Clearing (I <sub>2</sub> T)		180 at 700 V
<b>Product specifications</b>		
Application		Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator		Non Indicating
Fuse size		22 x 58 mm

**Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	700
Rated voltage DC	V	700
Rated current	A	20
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	6
Mounting holes		M6
Centre-to-centre distance of connections	mm	63.35