



Fuse-link, high speed, 25 A, AC 700 V, 200 kA, 14 x 51 mm, aR, UL, with striker

Part no. **25A 690V 14X51 INDICATED 14.3 X 50.8MM**
 Catalog No. **FWP-25A14FI**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	25
Rated voltage			AC 700 V
Size			14 x 51 mm
Utilization category			aR
Status indicator			with striker
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL 248
Optional accessories			fuse-holder CH141B

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Model			EV008881
Size			14x51 mm
Voltage type			AC/DC
Rated current			25
Rated voltage			690
Utilization category			aR (accompanied semiconductor protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			EV007782
Release characteristic			Other
Breaking capacity		kA	200
Power loss at rated current			7