



Fuse-link, high speed, 350 A, AC 700 V, DC 700 V, 200 kA, 51 x 130 mm, UL



**Part no.** BUSS HIGH SPEED FUSE  
**Catalog No.** FWP-350A

## Delivery program

|                              |   |    |  |
|------------------------------|---|----|--|
| Product range                |   |    | Fuse   |
| Basic function               |   |    | Fuse-link  |
| Field of application         |   |    | high speed   |
| Rated current                | I | A  | 350  |
| Rated voltage                |   |    | AC 700 V<br>DC 700 V   |
| Size                         |   |    | 51 x 130 mm  |
| Breaking Capacity            |   | kA | 200  |
| usable for size/applications |   |    | DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval            |   |    | UL   |
| Shape                        |   |    | cylindrical with centre-bolted tags  |
| Standards/Regulations        |   |    | UL 248   |

## Technical data ETIM 7.0

|   |  |    |       |
|---|--|----|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |       |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |       |
| Construction size   |  |    | Other |
| Rated current   |  | A  | 350   |
| Rated voltage   |  | V  | 700   |
| Voltage type  |  |    | AC/DC |
| Rated switching capacity  |  | kA | 200   |
| Utilization category  |  |    | Other |
| Type of fuse status indicator   |  |    | None  |
| Insulated metal gripping lugs (IMGL)  |  |    | No    |

## Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (web) | <a href="http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/high_speed_north_american/fwp.html">http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/high_speed_north_american/fwp.html</a> |
|-------------------------|---|