



Fuse-link, high speed, 40 A, AC 700 V, 14 x 51 mm, aR, UL, with striker

**FWP-40A14FI**

Similar to illustration

General specifications		
Product name		Eaton Bussmann series high speed cylindrical fuse
Part no.		FWP-40A14FI
EAN		5027590500722
Product Length/Depth		52 millimetre
Product height		15 millimetre
Product width		15 millimetre
Product weight		20.4 gram
Compliances		CE Marked RoHS Compliant
Certifications		UL Recognized CSA Certified
Product Tradename		None
Product Type		High speed cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		40 A
Voltage rating		700 V
Voltage type		AC/DC
Interrupt rating		200 kAIC
Class		Class aR
Clearing (I2T)		750
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator		Top fuse status indicator
Fuse size		14 x 51 mm
Fitted with:		Striker
Quantity		10

**Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		14x51 mm
Voltage type		AC/DC
Rated current	A	40
Rated voltage	V	700
Utilization category		aR (accompanied semiconductor protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Top fuse status indicator
Release characteristic		Other
Breaking capacity	kA	200
Power loss at rated current	W	8