

## Fuse-link, high speed, 4 A, AC 700 V, 14 x 51 mm, aR, UL



## FWP-4A14F

Similar to illustration

Product name	Eaton Bussmann series high speed cylindrical fuse
Part no.	FWP-4A14F
EAN	5027590500814
Product Length/Depth	52 millimetre
Product height	15 millimetre
Product width	15 millimetre
Product weight	20.4 gram
Compliances	RoHS Compliant CE Marked
Certifications	CSA Certified UL Recognized
Product Tradename	None
Product Type	High speed cylindrical fuse
Product Sub Type	None
lectrical data	
Amperage Rating	4 A
Voltage rating	700 V
Voltage type	AC/DC
Interrupt rating	200 kAIC
Class	Class aR
Clearing (I2T)	0.23
roduct specifications	
Application	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator	Non Indicating
Fuse size	14 x 51 mm
Quantity	10
ompatible microswitch	
Accessories	CH14 Modular fuse holder

## **Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])					
Model			Ceramic fuse		
Size			14x51 mm		
Voltage type			AC/DC		
Rated current	Į.	A	4		
Rated voltage	١	V	700		
Utilization category			aR (accompanied semiconductor protection)		
Rated operating frequency	H	Hz	45 - 62		
Type of fuse status indicator			Other		
Release characteristic			Other		
Breaking capacity	k	kA	200		
Power loss at rated current	V	W	3		