



Fuse-link, 500 A, AC 700 V, DC 700 V, 200 kA, 64 x 180 mm, UL

Part no. BUSS HIGH SPEED FUSE
Catalog No. FWP-500A

Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	500
Rated voltage			AC 700 V DC 700 V
Size			64 x 180 mm
Breaking Capacity		kA	200
usable for size/applications			DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical with centre-bolted tags
Standards/Regulations			UL 248

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	500
Rated voltage		V	700
Voltage type			AC/DC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/high_speed_/north_american/fwp.html
-------------------------	---