



Fuse-link, high speed, 50 A, AC 700 V, 200 kA, 14 x 51 mm, aR, UL

Part no. 50AMP 700V AC FERRULE 14 X 51 MM
Catalog No. FWP-50A14F

Delivery program

| | | | |
|------------------------------|---|----|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 50 |
| Rated voltage | | | AC 700 V |
| Size | | | 14 x 51 mm |
| Utilization category | | | aR |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval | | | UL |
| Shape | | | cylindrical |
| Standards/Regulations | | | UL 248 |
| Optional accessories | | | fuse-holder CH141B |

Technical data ETIM 8.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecI@ss10.0.1-27-14-20-01 [AFZ796015]) | | | |
| Model | | | Ceramic fuse |
| Size | | | |
| Voltage type | | | AC/DC |
| Rated current | | A | 4 |
| Rated voltage | | V | 700 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Rated operating frequency | | Hz | 45 - 62 |
| Type of fuse status indicator | | | Other |
| Release characteristic | | | Other |
| Breaking capacity | | kA | 200 |
| Power loss at rated current | | W | 9 |