



Fuse-link, high speed, 50 A, AC 690 V, 22 x 58, gR, IEC, UL, with striker



FWP-50G22FI

General specifications		
Product name		Eaton Bussmann series high speed cylindrical fuse
Part no.		FWP-50G22FI
EAN		5027590500944
Product Length/Depth		58 millimetre
Product height		22 millimetre
Product width		22 millimetre
Product weight		53.2 gram
Compliances		CE Marked RoHS Compliant
Certifications		UL Recognized IEC Rated
Product Tradename		None
Product Type		High speed cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		50 A
Voltage rating		690 V
Voltage type		AC
Interrupt rating		200 kAIC
Class		Class gR
Clearing (I ₂ T)		1362
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator		Top fuse status indicator
Fuse size		22 x 58 mm
Fitted with:		Striker
Compatible microswitch		
Accessories		CH22 Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	50
Rated voltage	V	690
Utilization category		gR (general purpose semiconductor protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Top fuse status indicator

Release characteristic		Other
Breaking capacity	kA	200
Power loss at rated current	W	11.85