

## Fuse-link, high speed, 5 A, AC 700 V, DC 700 V, 15 x 73 mm, UL



## FWP-5B

Similar to illustration

General specifications	
Product name	Eaton Bussmann series high speed cylindrical fuse
Part no.	FWP-5B
EAN	5027590500982
Product Length/Depth	60 millimetre
Product height	40 millimetre
Product width	86 millimetre
Product weight Product weight	25.4 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Recognized CSA Certified
Product Tradename	None
Product Type	High speed cylindrical fuse
Product Sub Type	None
Electrical data	
Amperage Rating	5 A
Voltage rating	700 Vac, 700 Vdc (UL)
Voltage type	AC
Interrupt rating	50 kAIC at 700 Vdc 200 kAIC Vac
Class	Class aR
Clearing (I2T)	10 at 700 V
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator	Non Indicating

## **Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016]) Fuse system according to IEC 60269 Other Fuse construction type according to IEC 60269 Other Type of current AC/DC Rated voltage AC ٧ 700 Rated voltage DC 700 5 Rated current Α Utilization category aR (accompanied semiconductor protection) kA Breaking capacity 50 None Colour code Type of fuse status indicator None W 1.5 Power loss at rated current Mounting holes M6 Centre-to-centre distance of connections 63.35