

Fuse-link, high speed, 60 A, AC 700 V, DC 700 V, 21 x 112 mm, aR, UL, with



FWP-60BI

Similar to illustration

| General specifications | |
|------------------------|--|
| Product name | Eaton Bussmann series high speed cylindrical fuse |
| Part no. | FWP-60BI |
| EAN | 5027590501002 |
| Product Length/Depth | 111 millimetre |
| Product height | 21 millimetre |
| Product width | 30 millimetre |
| Product weight | 107.2 gram |
| Compliances | RoHS Compliant |
| Product Tradename | None |
| Product Type | High speed cylindrical fuse |
| Product Sub Type | None |
| Electrical data | |
| Amperage Rating | 60 A |
| Voltage rating | 700 Vac, 700 Vdc (UL) |
| Voltage type | AC/DC |
| Interrupt rating | 200 kAIC Vac 50 kAIC at 700 Vdc |
| Product specifications | |
| Application | Semiconductor, DC Common bus, DC drives, Power converters/rectifiers |
| Fuse indicator | Non Indicating |

Technical data ETIM 9.0

| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | | | | |
|--|--|----|-------|--|--|
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016]) | | | | | |
| Fuse system according to IEC 60269 | | | Other | | |
| Fuse construction type according to IEC 60269 | | | Other | | |
| Type of current | | | AC/DC | | |
| Rated voltage AC | | V | 700 | | |
| Rated voltage DC | | V | 700 | | |
| Rated current | | Α | 60 | | |
| Utilization category | | | Other | | |
| Breaking capacity | | kA | 200 | | |
| Colour code | | | None | | |
| Type of fuse status indicator | | | None | | |
| Power loss at rated current | | W | 15.5 | | |
| Mounting holes | | | M8 | | |
| Centre-to-centre distance of connections | | mm | 90 | | |
| | | | | | |