



Fuse-link, high speed, 700 A, AC 700 V, DC 700 V, 51 x 169 mm, UL

**FWP-700A**

<b>General specifications</b>		
Product name		Eaton Bussmann series high speed cylindrical fuse
Part no.		FWP-700A
EAN		5027590021838
Product Length/Depth		56 millimetre
Product height		53 millimetre
Product width		180 millimetre
Product weight		588 gram
Compliances		CE Marked RoHS Compliant
Certifications		UL Recognized CSA Certified
Product Tradename		None
Product Type		High speed cylindrical fuse
Product Sub Type		None
<b>Electrical data</b>		
Amperage Rating		6 A
Voltage rating		700 Vac, 700 Vdc (UL)
Voltage type		AC
Interrupt rating		50 kAIC at 700 Vdc 200 kAIC Vac 200 kAIC
Class		Class aR
Clearing (I <sub>2</sub> T)		300000 at 700 V
<b>Product specifications</b>		
Application		Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator		Non Indicating

**Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	700
Rated voltage DC	V	700
Rated current	A	6
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	122
Mounting holes		Other
Centre-to-centre distance of connections	mm	134.95