

Fuse-link, high speed, 70 A, AC 700 V, DC 700 V, 25 x 112 mm, aR, UL



FWP-70B

Similar to illustration

General specifications	
Product name	Eaton Bussmann series high speed cylindrical fuse
Part no.	FWP-70B
EAN	5027590021821
Product Length/Depth	112 millimetre
Product height	25 millimetre
Product width	25 millimetre
Product weight	108 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Recognized CSA Certified
Product Tradename	None
Product Type	High speed cylindrical fuse
Product Sub Type	None
Electrical data	
Amperage Rating	700 A
Voltage rating	700 Vac, 700 Vdc (UL)
Voltage type	AC/DC
Interrupt rating	50 kAIC at 700 Vdc 200 kAIC Vac
Class	Class aR
Clearing (I2T)	2000 at 700 V
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator	Non Indicating

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016]) Fuse system according to IEC 60269 Other Fuse construction type according to IEC 60269 Other Type of current AC/DC Rated voltage AC ٧ 700 Rated voltage DC 700 700 Rated current Α Utilization category aR (accompanied semiconductor protection) kA Breaking capacity 200 None Colour code Type of fuse status indicator None W 18 Power loss at rated current Mounting holes M8 Centre-to-centre distance of connections 91.5