

Fuse-link, high speed, 900 A, AC 700 V, DC 700 V, 89 x 193 mm, aR, UL



FWP-900A

General specifications	
Product name	Eaton Bussmann series high speed cylindrical fuse
Part no.	FWP-900A
EAN	5027590021890
Product Length/Depth	193 millimetre
Product height	89 millimetre
Product width	89 millimetre
Product weight	3064 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Recognized CSA Certified
Product Tradename	None
Product Type	High speed cylindrical fuse
Product Sub Type	None
Electrical data	
Amperage Rating	8 A
Voltage rating	700 V (UL)
Voltage type	AC
Interrupt rating	200 kAIC Vac 50 kAIC at 700 Vdc 200 kAIC
Class	Class aR
Clearing (I2T)	530000 at 700 V
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator	Non Indicating

Technical data ETIM 9.0

Iconnical data Ethii 3.0		
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installatio	n, device / Safety fuse	inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	700
Rated voltage DC	V	700
Rated current	Α	8
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	150
Mounting holes		Other
Centre-to-centre distance of connections	mm	151.61