



Fuse-link, LV, 175 A, AC 600 V, 22 x 83 mm, T, UL, very fast acting

Part no. TRON FAST ACTING FUSE CLASS T
Catalog No. JJS-175

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	175
Rated voltage			AC 600 V
Size			22 x 83 mm
Utilization category			T
Breaking Capacity		kA	200
usable for size/applications			commonly applied in electric heat circuits, load center, disconnect switches, and meters
Release characteristic	class		very fast acting
Standard/Approval			UL

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	175
Rated voltage		V	600
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1029_JJS.pdf
Product overview (WEB)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/class_t/jjs.html