



Fuse-link, LV, 20 A, AC 600 V, 10 x 38 mm, CC, UL, fast acting, rejection-type

Part no. **CLASS CC FAST ACTING FUSE CLASS CC**
 Catalog No. **KTK-R-20**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	20
Rated voltage			AC 600 V
Size			10 x 38 mm
Utilization category			CC
Description			rejection-type
Breaking Capacity		kA	200
usable for size/applications			branch circuit
Release characteristic	class		fast-acting
Standard/Approval			UL
Shape			cylindrical

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			10x38 mm
Rated voltage		V	600 - 600
Rated voltage			Other
Voltage type			AC
Utilization category			Other
Rated operating frequency		Hz	45 - 62
Nominal current		A	20
With striker			No
Release characteristic			CC
Breaking capacity		kA	200

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1015_KTK-R.pdf
Product overview (WEB)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/fuses_class_cc_j_rk1_rk5/class_cc/ktk-r1.html