



**Fuse-link, low voltage, 100 A, AC 600 V, DC 300 V, 300 kA, 29 x 118 mm, J, UL, with indicator, time-delay**

**Part no. INDICATING LPJ-100SP**  
**Catalog No. LPJ-100SPI**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	100
Rated voltage			AC 600 V DC 300 V
Size			29 x 118 mm
Utilization category			J
Status indicator			with indicator
Breaking Capacity		kA	300
usable for size/applications			Specialized circuits and industrial control
Release characteristic	class		time-delay
Standard/Approval			UL
Time delay			time-delay 10 seconds (minimum) at 500% of rated current

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	100
Rated voltage		V	600
Voltage type			AC/DC
Rated switching capacity		kA	300
Utilization category			Other
Type of fuse status indicator			Centre fuse status indicator
Insulated metal gripping lugs (IMGL)			No

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1007_LPJ_70-600.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1007_LPJ_70-600.pdf</a>
-------------------------	---